



NOTE: THE OVERLOAD CAPACITIES FOR BENDING MOMENT, AXIAL AND RADIAL FORCE EXCEED 300% OF THOSE USED FOR CROSSTALK MEASUREMENT

DRAWING IN THIRD ANGLE PROJECTION

\* LOW VOLTAGE OUTPUT AMPLIFIER IS NOT INCLUDED

### SPECIFICATIONS

CAPACITY (Nm)	40
OVERLOAD CAPACITY (%F.S.)	300
OUTPUT @ F.S. NOMINAL	1.0 MV/V
POWER SUPPLY (V)	4.5 TO 5V
BRIDGE RESISTANCE ( $\Omega$ ) NOMINAL	350
NON-LINEARITY (%F.S.)	0.5
HYSTERESIS (%F.S.)	1.0
OPERATING TEMP. RANGE ( $^{\circ}$ C)	-20 TO +100
CROSSTALK (%F.S.)	1.0
AXIAL FORCE FOR CROSSTALK (N)	250
RADIAL FORCE FOR CROSSTALK (N)	250
BENDING MOMENT FOR CROSSTALK (Nm)	20
TORSION ANGLE (CALCULATED)	0.04 $^{\circ}$
TORSIONAL STIFFNESS (KNm/RAD)	60
BENDING STIFFNESS (KNm/RAD)	10
MASS (KG)	0.05

### WIRING CODE

COLOR	FUNCTION
RED	+EX
GREEN	+SIG
BLACK	GND
BROWN	-SIG

**SUNRISE INSTRUMENTS**

[www.srisensor.com](http://www.srisensor.com)

SINGLE AXIS TORQUE LOADCELL  
D41MM, 40 Nm

UNLESS OTHERWISE SPECIFIED  
DIMENSIONS ARE IN MM

M2210S

REV.  
0.2